

Model **PTF**

Advantages:

Standard type pallet truck

- Chrome piston and ram for smooth operation and prevents excessive wear on the pump & seal.
- Excellent turning angle of 180 degrees facilities.
- Number of pump strokes - 10 times. Lift height per stroke: 11 mm.
- Option: 1) Nylon wheel, polyurethane wheel, rubber wheel, single fork roller or tandem fork rollers.
2) Fork length: 800mm, 900mm, 1000mm.



Conforms to EN ISO3691-5
Based on Directive 2006/42/EC

1KG = 2.205 LB 1INCH = 25.40 MM

Model		PTF	
Capacity	Q(kg)	2500/3000	2500/3000
Lowered fork height	h ₁₃ (mm)	85	75
Steering wheel	mm	φ180	φ160
Fork wheel single	mm	φ70x80	φ70x80
Fork wheel tandem	mm	φ70x60	φ70x60
Max. lifting height	h ₃ (mm)	200	190
Total Height	h ₁₄ (mm)	1186.5	1176.5
Overall length	l ₁ (mm)	1520/1590	1520/1590
Fork length	l(mm/)	1150/1220	1150/1220
Fork Width	e(mm)	150	150
Width Overall forks	b ₅ (mm)	520/550/680	520/550/680
Ground clearance, centre of wheelbase	m ₂ (mm)	32	22
Aisle width for pallets 1000x1200 crossways	A _{st} (mm)	1720/1790	1720/1790
Aisle width for pallets 800x1200 lengthways	A _{st} (mm)	1770/1790	1770/1790
Turning radius	W _a (mm)	1265/1335	1265/1335
Service weight	kg	55/65	55/65

Remark: (1) Capacity 2000 kg available.

(2) Special size fork width and length can be made according to customers requirement.

